

# C 61 Multicore Instrument Cable, With Electrical Screen

## Insulation material

Each wire and overall jacket high quality extruded

### Please specify

P : for PVCPE : for Polyethylene

### Individual shield

Aluminium mylar tape, 100% coverage Earthwire tinned copper 0.8 mm. solid ( C ) or stranded 7 x 0.31 mm. / 0.5 mm<sup>2</sup> ( D )

### Shape

Round

### Moisture resistance

Good

### Flame resistance

Good

### Temperature limits

PVC : -30 / +105 ° CPE : -30 / +70 ° C

## Conductors

Stranded copper

### Conductor size

0.51 mm<sup>2</sup>, 7 x 0.3 mm ( 20 Awg )

### Number of pairs

2, 4, 6, 10, 12, 16, 20, 24, 36 or 48

### Number of triads

2, 3, 4, 6, 8, 10, 12, 20 or 24

### Construction

Twisted, ± 20 times per meter

### Identification

Pair or Triad ( P or T ), numbered Triad : Black, white and red, numbered

### Jacket colour


Black or blue

### Please specify

## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model



Insulation ( P or PE )

Earth wire ( C or D )

Number of pairs / triads

Pair or Triad ( P or T )

Jacket colour

H8-1 Rev. 07/07