

# HM5030 AINiCo Horseshoe magnetic surface thermocouple

## Construction

Magnet	Horseshoe AINiCo magnet
Magnet dimensions	39x26x25mm (LxWxH)
Ingress protection	IP54

## Cable

Type	PTFE insulated cable std. Silicon optional
Cable length	4000mm standard

## Thermocouple

Calibration	K, T or J
Accuracy	According IEC 584-1
Duplex type	KK, TT or JJ
Hot junction	Free from ground
Insulation test	Minimum 100 Mohm

## Temperature limit

Maximum temperature	Measuring tip maximum 240°C
---------------------	-----------------------------

## Options

Cable	Other cable type
ATEX	Exi, Exe or Exd
Contact	Sensitive surface contact Spring loaded
Transport protection	Metal frontplate, must be removed to measure
Magnetic strength	90 Newton



## Thermokoppel kleurcodes

Thermocouple Extension Type	ANSI	IEC
JX + Iron - Constantan ®		
KX + Chromel ® - Alumel ®		
TX + Copper - Constantan ®		
EX + Chromel ® - Constantan ®		
NX + Nicrosil ® - Nisil ®		
SX + Copper RX - Alloy 11		
BX + Copper-S - Copper-E		


## Toleranties volgens IEC 584-2

Type	Class	Temperature range	Fixed value °C	Tolerance to temp. t (°C)
T	1	- 40°C to + 350°C	± 0,5	± 0,004 · t
	2	- 40°C to + 350°C	± 1	± 0,0075 · t
	3	- 200°C to + 40°C	± 1	± 0,015 · t
E	1	- 40°C to + 800°C	± 1,5	± 0,004 · t
	2	- 40°C to + 900°C	± 2,5	± 0,0075 · t
	3	- 200°C to + 40°C	± 2,5	± 0,015 · t
J	1	- 40°C to + 750°C	± 1,5	± 0,004 · t
	2	- 40°C to + 750°C	± 2,5	± 0,0075 · t
	3	-	-	-
K and N	1	- 40°C to + 1000°C	± 1,5	± 0,004 · t
	2	- 40°C to + 1200°C	± 2,5	± 0,0075 · t
	3	- 200°C to + 40°C	± 2,5	± 0,015 · t
R and S	1	0°C to + 1600°C	± 1,0	± [1+0,003·(t-1100)]°C
	2	0°C to + 1600°C	± 1,5	± 0,0025 ·t
	3	-	-	-
B	1	-	-	-
	2	+ 600°C to + 1700°C	± 1,5	± 0,0025 ·t
	3	+ 600°C to + 1700°C	± 4	± 0,005 ·t

## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model



Thermocouple type

Cable length (4000mm standard)

H1-1 Rev.0 7/07