

Explosionproof ATEX Ex-i digital thermocouple thermometer

Specifications / Approval

ATEX approval	Intrinsically safe zone 1 Gas, II 2 G Ex ib IIB T4 Gb
Certificate	TÜV 13 ATEX 117115 X

Input

Thermocouple selectable	Type J, K, L, N, T
Standard	According IEC 60584-1
Measuring range	-200°C up to 1370°C
Resolution	0.1 degree over the full range

Accuracy

-40°C...+200°C	±0,2°C with internal cold junction compensation
200°C up to 1000°C	±0,5°C with internal cold junction compensation
>1000°C	±1,0°C with internal cold junction compensation

Model numbers

P710	1-Channel input
P715	2-Channel input

Functions

Measuring rate	1 to 4 measurements per second
Memory	Min./Max. memory, Hold
Function selection	With keypad
Display	LCD 4 1/2 digit 1 or 2 lijns

Power supply

Battery	9 Volt
Battery life	Auto power off function, typical 20 hours continue.
Ambient temperature	0 to 40°C
Storage temperature	-10 to 50°C

Housing

Material	Sturdy ABS
Dimensions	200 x 93 x 44mm
Weight	Instrument weight 300 gram
Sensor connection	8-Pole DIN connector

Options

Carrying case	Suitable for Instrument and probe
----------------------	-----------------------------------

Thermocouple probes

LCD backlighting	Green LED illumination
Models	Surface probes (Contact and Magnetic) Insertion probes Liquid/Gas Air / Gas probes Tank probe with cable

Probes to choose Please contact us for the right probe for your application

Units Selectable °C / °F



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

